WASHINGTON COUNTY

Date: 09/29/14



Building Services, Department of Land Use & Transportation 155 N. First Ave., Suite 350-12, Hillsboro, OREGON 97124-3072


Building Services Engineering Guide 5

Retaining Wall Permit Requirements per OSSC Section 105.1, 1601, 1803.5.12, and 1807

General: Retaining walls are designed to resist loads due to lateral pressure of retained material, i.e. soil and seismic in accordance with accepted engineering practices and Oregon Structural Specialty Code (OSSC) provisions 105.1. Building permits are generally required for retaining walls depending on the wall height, the loading conditions or both as shown in cases 1 to 5 below.


Case-1: Retaining wall that is **4-feet or less** in height as measured from bottom of foundation to top of wall with level back fill as shown. Building permit is not required per the Community Development Code 419-4.


Case-5: When 7-ft fence wall made of wood, vinyl or chain-link fence placed on top of Case-1 retaining wall condition as shown in Case-5 making a total or combined height of 11-ft, building permit is not required for this case per OSSC 105.2 items 2 and 4.




Cases-2 to 5: All retaining wall conditions with the exception of Case-1 and 5 condition as described above requires a building permit and shall be designed by a Registered Design Professional (RDP) to meet OSSC 1601 provisions. The following information is required for review and approval:


- Site plans showing wall layout, crosssections and structural details stamped by a RDP.
- 2. Calculations and structural details stamped by a **RDP** (Without sitespecific geotechnical report, design pressure for cantilevered (unrestrained) and basement (restrained) type of walls are 40psf and 55psf respectively).
- Periodic special inspection during construction may be required per OSSC 1701 provisions.











Case-5: Fence on Retaining Wall

Mission Statement