



Department of Land Use & Transportation
 Planning and Development Services
 Building Services
 155 N First Avenue, Suite 350, MS 12
 Hillsboro, OR 97124-3072
 503-846-3470, fax: 503-846-3993
 email: lutbldg@co.washington.or.us

High Efficiency Interior Lighting Systems

Permit #: _____ Project #: _____ City: _____
 Site Address: _____ TaxLot ID: _____
 Subdivision: _____ Lot: _____

By my signature below, I certify that all of the permanently installed lighting fixtures in the above mentioned building have been installed with compact or linear fluorescent, or a lighting source that has a minimum efficacy of 40 lumens per input watt. (Oregon Residential Specialty Code N1107.2^[1]) Exception: Two permanently installed lighting fixtures are not required to have high-efficiency lamps.

Signature: _____ Date: _____
 Owner/General Contractor/Authorized Agent
 Print Name: _____

^[1]ORSC Section N1107.2. High-efficiency interior lighting systems. All of the permanently installed lighting fixtures shall be installed with compact or linear fluorescent, or a lighting source that has a minimum efficacy of 40 lumens per input watt. Screw-in compact fluorescent lamps comply with this requirement.

The building official shall be notified in writing at the final inspection that all of the permanently installed lighting fixtures are compact or linear fluorescent, or a minimum efficacy of 40 lumens per input watt.

-----tear at perforation-----



Department of Land Use & Transportation
 Planning and Development Services
 Building Services
 155 N First Avenue, Suite 350, MS 12
 Hillsboro, OR 97124-3072
 503-846-3470, fax: 503-846-3993
 email: lutbldg@co.washington.or.us

Moisture Sensitive Wood Framing Moisture Content

I, _____, am the general contractor or the owner/builder at the following Address:

Permit #: _____ Project #: _____ City: _____
 Address: _____ TaxLot ID: _____
 Subdivision: _____ Lot: _____

Oregon Residential Specialty Code (ORSC), Section R318.2, I am notifying the building official that I am aware of the moisture content requirement of ORSC Section R318.2 and have taken steps to meet this code requirements.

Section R318.2 Moisture Content. Prior to issuance of the insulation/vapor barrier approval required by R109.1.5.2 of this code.

- (A) All moisture-sensitive wood framing members used in construction shall have a moisture content of not more than 19 percent of the weight of dry wood framing members.
- (B) The general contractor of the owner who was issued the structural permit shall notify the building official on a division-approved form that the contractor or the owner who was issued the structural permit is aware of and has taken steps to meet the requirement in paragraph (A).

Signature: _____ Date: _____
 Owner/General Contractor/Authorized Agent